



GATEWAY office furniture



User's Manual

5CSBOOTHBK
5CSBOOTHWH

CONTENTS

I SPECIFICATION

- 1.1 General
- 1.2 Parts & material
- 1.3 Wiring diagram
- 1.4 Dimmer controller-optional
- 1.5 Internal power supply

II ATTENTION

- 2.1 Installtion
- 2.2 Electricity
- 2.3 Daily use

III INSTALLATION INSTRUCTION

- 3.1 Before start
- 3.2 Parts list
- 3.3 Booth installation
- 3.4 Check list
- 3.5 Trouble shooting

IV MAINTENANCE

- 4.1 Regular maintenance instruction
 - 4.2 Warranty card
-

SPECIFICATION I

1.1 GENERAL

Ext.size	1030*1030*2275 mm / 40.6X40.6X89.6 in.
Int.size	906*906*2170 mm / 35.7X35.7X85.4 in.
Floorspace	1SQM(10.76 sq.ft.)
Degree of opening	90° With door closer.
Packaging size	W2270mm(89.3')XD1100mm(43.3")XH625mm(24.6")
Net./Gr.weight	360kg(793.4lbs)
Power input	100-240V/50-60Hz power supply.
Ventilation	Total air flow is 144.08m³/h; Air Replaced every 0.85 minute.
Lighting	Inductive LED-Light 4000 K.
Consumption	Use power 9.6W; standby power 1W;
Power supply	4 hole universal outlet×2,USB Type A×1,USB Type C×1
Sound proofing	STC 30dB (±5dB) IN ASTM E565-96
Operational noise	<30dB when running in default setting

SPECIFICATION I

1.2 Parts & material

Major materials and accessories	Frame	6063-T5 aviation aluminnum alloy,High quality Power electrostatic spraying. (As per AAMA 2603)
	Glass	5+5mm laminated tempered Glass,edge with Baking paint;
	Side Modules	9MM Acoustic panel + 0.8MM galvanized steel plate + 50MM acoustic cotton + 6MM gypsum board + 1.0MM galvanized steel plate (inside to outside);
	Ceiling Modules	9MM Acoustic panel + 0.8MM galvanized steel plate + 50MM acoustic cotton + 1.0MM galvanized steel plate (inside to outside);
	Carpet	Nylon fiber carpet with PVC base;
	Door lock	Griff door handle and standard lock;
	Hinge	Aluminum detachable barrel hinge,steel pin,brass bearing,3.0mm leaf,fast-deploy;
	Door closer	Concealed cam-action door closer.

